

**T H E R M O M E T R I C S**  
A COMMITMENT TO EXCELLENCE  
AN AMPHENOL COMPANY

# Type PTO Series PTC Thermistors



## Description

Thermometrics PTO series consists of a range of radially-wire bare PTC disc thermistors.

## Features

- Solid state sensor
- Available in a broad range of resistances, transition temperatures and voltage ratings
- Exhibits large positive increases in resistance with temperature
- Resistance/temperature characteristic is infinitely repeatable and has no hysteresis associated with its action
- Proven quality and reliability over many years of manufacturing

## Applications


- Current regulation
- Circuit protection
- Temperature control

# Amphenol

## Sensors

Operating Voltage, $V_{max}$	Part Number	Replacement for	R @ 25°C ( $\pm 30\%$ ) $\Omega$	Switch Temperature, $T_b$	A (max) mm	B (max) mm	C (ref) mm	D (ref) mm	L (min) mm
12	YS5893PTO	RL5305-2.5-110-12-PTO	2.5	120°C	15.24	4.06	8.38	0.8	38.1
12	YS5898PTO	RL3005-25-110-12-PTO	25	120°C	8.89	3.81	6.35	0.5	38.1
25	YS5745PTO	RL3006-50-40-25-PTO	50	40°C	8.89	3.81	6.35	0.5	38.1
120	YS5917PTO	RL6010-20-120-120-PTO	20	120°C	16.51	5.84	8.38	0.8	38.1
120	YS5918PTO	RL5510-25-60-120-PTO	25	60°C	15.24	5.59	8.38	0.8	38.1
120	YS5921PTO	RL2510-200-110-120-PTO	200	120°C	7.62	5.08	3.81	0.6	38.1
240	YS5925PTO	RL6015-100-120-240-PTO	100	120°C	16.51	6.86	8.38	0.8	38.1
240	YS5930PTO	RL3020-3000-100-240-PTO	3K	100°C	8.89	7.87	6.35	0.8	38.1
480	YS5934PTO	RL3020-5K-100-480-PTO	5K	100°C	8.89	7.87	6.35	0.8	38.1

## Mechanical Specifications



## Electrical Specifications

### Ambient Temperature Range

**At Storage:** -25 to +155°C

**At Maximum Voltage:** +10 to +55°C

### Construction

Bare ceramic disc

Thick silver film electrodes

Uninsulated leadwires

### Terminations

Straight type, tin coated copper wire

**Amphenol**  
**Sensors**

[www.amphenol-sensors.com](http://www.amphenol-sensors.com)

© 2025 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.